

Description: Durable, weather-resistant, decorative and multicoloured granolithic finish based on acrylic resin dispersion. Breathable, impact-resistant and easy to apply. For interior and exterior use.

Use: Suitable substrates include, for example, all smooth and even surfaces such as: concrete, brick, cement and plasterwork, existing coats of paint, plasterboard, board, fine float finish, etc.

Properties:

- Durable and weather-resistant
- Shock-resistant
- Excellent adhesion
- Easy to apply
- Breathable

Colour: In various colours according to the Granite plaster colour samples. For optimum coverage of darker colours, use SPS Plaster pretreatment in a colour that is tailored to the colour of the final coat.

Application:

Mix thoroughly prior to use. Dilute with a maximum of 3% water if necessary. Apply evenly using a stainless steel plastering trowel with a thickness that matches the grain. Then brush smooth using a stainless steel plastering trowel. Do not brush smooth for too long in the same place, as this may cause grey/dull patches.

Covers:

- 1.5 mm Fine: approximately 2.7 kg/m²
- 3 mm Coarse: Approximately 4.5 kg/m²

The stated coverage is theoretical. Actual consumption depends on the nature and the structure of the surface and the application method.

Drying time at 23°C and relative humidity 65%:

Dry after approximately 6 hours.

Cures after a few days.

Variations in temperature, relative humidity etc. affect the drying time.

System structure

General:

The substrate must be smooth and even, capable of supporting the paint, completely set, clean, dry, and free of dust or grease. Sand and repair surface irregularities. Remove and/or repair all loose and unstable coats. When using externally, remove all algae and moss.

Prime first using SPS Plaster pretreatment before applying SPS Plaster pretreatment.

New, untreated substrate

- Plasterboard boards: Mask seams with plaster tape and seal using a suitable filler.
- Gypsum plasterwork: Carefully remove paint.
- Thoroughly clean powdery surfaces. Prime with a fixator after allowing to dry.

Existing, load-bearing substrates:

- Clean surface.
- Smooth and even out (structured) surface.

Existing, non-load-bearing substrate:

- Thoroughly remove loose coats.
- Thoroughly wash powdery coats and allow to dry.
- Carry out any repairs.
- Prime with a fixator.
- Smooth and even out (structured) surface.

Contamination caused by nicotine, damp, rust or soot:

- Clean thoroughly.
- Treat surface/contamination using a sealing primer.

The aforementioned systems form a general description of the most common substrates. Please contact SPS bv for specific applications and/or detailed advice.

TECHNICAL DATA

Binding agent:	100% acrylic resin dispersion
Pigments:	Coloured granite grains
Solvent:	Water
Solid components:	77 m/m %
Equivalent weight:	Approximately 1.75 g/ml
Degree of gloss:	Light satin gloss
Recommended coat thickness:	For each coat, apply with a thickness that matches the grain.
Hazard classification:	See MSDS
Tool cleaning instructions:	Use water and soap

Shelf life: Minimum 12 months in tightly closed original packing in a dry, cool and frost-free place.

General:

Do not use at temperatures below +8°C. Only use when the surface temperature is at least 3°C above the dew point temperature. Do not apply outdoors when it is likely to rain or when frost is expected. Do not apply outdoors in direct sun. When using this product, always use the necessary personal protective equipment. Do not inhale the spray or fumes from products. Always ventilate in a suitable way during use. There may be slight variations in colour since natural base materials are used. Please therefore blend pots with a different batch number prior to use.

Surplus product: This paint and the packaging should be disposed of at a collection point for hazardous or special waste.