

Description: Satin gloss, scratch-resistant, durable PU acrylate topcoat for a decorative finish of wood, hard plastics and metal. Skin fat resistant and quick drying.

Use: Suitable as topcoat on pre-treated wooden, plastic and metal surfaces.

Properties:

- Protects against skin greases
- Fade resistant and non-yellowing
- Water base

Colour: White, RAL 9010 and black.

Application: Stir well before use. Apply in one or more layers with a suitable brush or roller. Always work wet-on-wet to avoid visible strokes. Do not touch up during drying.

Covers: Approx. 16 m² / litre per layer. The specified yield is theoretical. Actual consumption depends on the nature and structure of the substrate and the processing method.

Drying time at 23°C and relative humidity of 65%:

Dry after approx. 1 hour.

Can be painted after approx. 20 hours.

Variations in layer thickness, temperature, humidity, etc. influence the drying time.

PAINT SYSTEM

General:

The substrate must be load-bearing, clean, dry, dust and grease free. For good edge coverage, the sharp corners of wooden window frames should be slightly rounded off.

Untreated wood: degrease, sand lightly and make it dust-free, then primer twice with SPS Uniprimer.

Existing old layers: Remove loose parts, degrease, sand, remove dust and first primer with SPS Uniprimer.

Metal: Degrease and make it rust and dust free. Treat with SPS Anti-Rust Primer, then an intermediate layer SPS Uni-Primer.

The systems described above apply for the most common types of surface. For specific applications and/or detailed advice, please contact SPS bv.

TECHNICAL DATA (applies to white)

Solvent:	Turpentine / white spirit
Solid components:	35% v/v
Specific mass:	Approx. 1,20 g/ml
Gloss level:	Satin gloss, 35-50% @ 60°
Dilute with:	Turpentine / white spirit
Hazard classification:	See MSDS
Tool cleaning instructions:	Water and soap

Shelf life:

Minimum of 12 months in the tightly sealed original packaging in a dry, cool and frost-free place.

General:

Do not apply at temperatures below +8°C. Only apply if the surface temperature is at least 3°C above the dew point temperature. Do not apply outdoors when it is likely to rain, when frost is expected or in direct sunlight. Always use the required personal protective equipment when applying this product. Always ventilate appropriately when applying.

Surplus product:

This paint and the packaging should be disposed of at a collection point for hazardous or special waste.