

Description: Water-based white acrylic primer for wall paint. Prevents variations in gloss, ensures better adhesion and paint coverage, prevents suction and improves efficiency of finishing coats. Solvent-free, low-odour and quick drying. For interior use.

Application: Suitable substrates are: Cement and plasterwork, concrete, brick, plasterboard, board, wallpaper etc.

Properties:

- Solvent-free and virtually odourless.
- Breathes
- Easily washable
- Matt.
- Good penetration
- Water-soluble

Colours: White

Handling: Stir thoroughly prior to use. Apply in 1 or 2 coats with a square pasting brush, woolly roller or airless spray. The first coat can be diluted with max. 10% water while the second coat should not be diluted.

Covers: According to DIN EN 13300 approx. 10 m²/litre per coat, depending on the surface.

Deposition efficiency: class 4

Drying time at 23°C and rel. humidity 65%:

Dust-dry after approx. 1 hours.
Recoatable after approx. 4-6 hours.

SYSTEM CONSTRUCTION

Substrate: The surface must have a bearing capacity, be clean, dry, and be free from dust or grease. Sand and repair surface irregularities. Remove and restore any loose and unstable coats.

New plasterwork: Prime with Finess Wall paint Primer.

Existing plasterwork: Clean using water and a degreasant. Allow to dry. Prime with Finess Wall paint Primer.

Powdering substrates: Clean thoroughly with clean water and allow to dry. Prime with Finess Stabilising Primer. Next, apply a coat of Finess Wall paint Primer.

Non water-resistant (rub-resistant) coats of paint:

Wash thoroughly until the surface does not flake or dust anymore. Next, prime with Finess Stabilising Primer. Next, apply a coat of Finess Wall paint Primer.

TECHNICAL DATA

Binding agent:	Acrylic dispersion
Pigments:	Rutile titanium dioxide and mineral fillers
Solvent:	Water
Solid components:	53 m/m %
S.M.:	1.37 g/ml
Viscosity:	40 Poise Brookfield Sp6/50rpm @ +20°C
Gloss degree:	ISO-2813 and DIN EN 13300: matt. 60/2.5% 85/15% according to Gardner
Tint:	White
Dilution:	Water
Hazard classification:	See MSDS
Cleaning instructions:	Use water and soap.

Features: Provides better adhesion to lightly powdering substrates. Eliminates substrate suction. Increases the efficiency of subsequent coats. Abrasion resistance to DIN EN 13300: Class 2

Storage: Minimum 12 months in tightly closed original packing in a dry, cool and frost-free place.

General: Do not use in temperatures below +8°C.

Do not apply outdoors when it is likely to rain or when frost is expected. Do not apply outdoors in direct sun. Allow newly cemented surfaces to set for at least 6 weeks.

Surplus product: Dispose of this material and its container to hazardous or special waste collection point.