

SPS



BETONCONTACT

pre-treatment primer

- Perfect adhesion
- For roller and brush application
- Water-dilutable
- High yield
- Alkali-resistant

BETONCONTACT

DESCRIPTION

Pink-tinted, alkali-resistant pre-treatment primer based on a synthetic resin dispersion mixed with pure quartz sand. Suitable for pre-treating impermeable, non-absorbent or minimally absorbent substrates such as untreated concrete, concrete enamel, gypsum blocks, etc. Forms an adhesion-enhancing bridge on surfaces which are not suitable for direct application of a plaster finishing coat. For interior use.

RECOMMENDED USE

As an adhesion promoter for gypsum plasters. SPS Concrete Contact is suitable for application on untreated, smooth and dense, weakly or non-absorbent mineral substrates.

RECOMMENDED SYSTEM

Existing load-bearing substrates- Carry out any repairs - Pre-treat completely with SPS Betoncontact. **Contamination by nicotine, moisture, rust or soot** Thoroughly clean - Carry out any repairs - Pre-treat completely with SPS Iso-Primer - Pre-treat completely with SPS Betoncontact after drying. The above systems are general descriptions for the most common substrates. For specific applications and/or detailed advice, please contact SPS bv.

DRY TIMES BY 20° C/RH 50%

Touch dry: Approx. 2 hours.
Dry to recoat: Approx. 24 hours.

RECOMMENDED WET FILM THICKNESS

Apply 1 thin layer, not excessively.

THEORETICAL CONSUMPTION

Approx. 160 - 300 g/m² (= 10 m²/l - 5 m²/l) per coat.

PRACTICAL CONSUMPTION

Actual consumption depends on the nature and structure of the substrate and the processing method.

SURFACE PREPARATION

The substrate must be, load-bearing, fully bonded, clean, dry, dust- and grease-free. Repair cracks and fissures. Remove and/or repair loose and unstable layers.

DIRECTIONS FOR USE

SPS Betoncontact is ready-to-use. Stir well before use. Apply evenly in one coat with a brush or roller.

APPLICATION CONDITIONS

Do not apply at temperatures below 8°C or above 30°C. Only apply when the temperature of the substrate is at least 3°C above the dew point temperature. Do not apply outdoors under threat of rain, frost, or in full sunlight.

APPLICATION & THINNING: BRUSH

Ready-to-use.

APPLICATION & THINNING: ROLLER

Ready-to-use.

CLEANING OF EQUIPMENT / SPILLS

With clean water.

REMARKS

Before use, consult the plaster supplier's instructions for the correct plaster and correct application.

SHELF LIFE

Minimum 12 months in tightly closed original container in dry, cool and frost-free place.

Date issued: 27/05/2026

Available colours & pack sizes: Please refer to the respective product page on www.rust-oleum.eu for an overview of actual available colours and pack sizes.

Disclaimer: The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Rust-Oleum Europe be liable for consequential or incidental damages. Products must be stored, handled, and applied under conditions complying with Rust-Oleum Europe recommendations detailed within the latest copy of the product data sheet. It is the users responsibility to ensure that they have the current copy. Latest copies of the product data sheet is available for free and downloadable from www.rust-oleum.eu or upon a request to our Customer Services department. Rust-Oleum Europe reserves the right to change the properties of its' products without prior notification.

Rust-Oleum Netherlands B.V.
Europalaan 9
5232 BC 's-Hertogenbosch
The Netherlands
T : +31 (0) 165 593 636
F : +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T : +44 (0)1914 113 146
F : +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chêne
95322 Herblay
France
T : +33(0) 130 40 00 44
F : +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Belgium
T : +32 (0) 13 460 200
F : +32 (0) 13 460 201
info@rust-oleum.eu

