

SPS



FAÇADE MAT SB

Matt silicone resin emulsion facade paint

- S.R.E.P. technology
- High water vapour permeability
- Dirt-repellent and rainproof
- Good protection against mould and algae

FAÇADE MAT SB

ОПИСАНИЕ

Has low dirt adhesion and high water vapour permeability/rainproofness due to S.R.E.P. technology (Silicon Resin Emulsion Paint). Optimal for a durable finish with high demands.

ПРЕПОРЪЧИТЕЛНА УПОТРЕБА

Due to its optimal water vapour permeability, it is particularly suitable for exterior walls with high moisture management requirements. Suitable substrates are: existing wall paint coats (mineral and synthetic), all mineral substrates such as cement and plaster, concrete, brick, etc.

ПРЕПОРЪЧИТЕЛНА СИСТЕМА

New, untreated substrates- Prime highly absorbent substrates completely with SPS Fix-Primer. -Thoroughly clean absorbent substrates. After drying, pretreat with Fix-Primer. - After drying, paint over. **Existing intact wall paint layers**- Clean with SPS Paint Cleaner. - Paint over the surface after drying. **Existing non-bearing wall paint layers**- Remove loose particles - Wash off powdery layers thoroughly and allow to dry - Carry out repairs if necessary - Pre-treat with SPS Fix-Primer - Paint off opaquely after drying. **Contamination by moisture, rust or soot**- Thoroughly clean with SPS paint cleaner - Treat the surface/contamination with SPS Iso-Primer. The listed systems apply as a general description for the most common substrates. For specific applications and/or detailed advice, please contact SPS bv.

ТЕХНИЧЕСКИ ДАННИ

Плътност (г/см³):	1.48
Гланцово ниво:	Мат
gloss_level_85:	6%
Съдържание на сухо вещество (по обем):	40%
water_vapour_permeability:	Sd= 0.02m

ВРЕМЕ ЗА СУШЕНЕ ДО 20° C/RH 50%

Сух на допир:	2 hours
Готов за повторно нанасяне:	4 - 6 hours
group_dry_40_full_cure:	Variations in layer thickness, temperature, humidity, etc. affect the drying time.

МОКЪР СЛОЙ

200

СУХ СЛОЙ

80

РАЗХОДНА НОРМА

Approx. 5 m² /litre per coat for optimum protection.

КОНСУМАЦИЯ

The stated yield is theoretical. Actual consumption depends on the nature and structure of the substrate and the processing method.

ПОДГОТОВКА НА ПОВЪРХНОСТТА

The substrate must be load-bearing, completely sealed, clean, dry, dust- and grease-free. Repair cracks and fissures. Remove and/or repair loose and unstable layers and remove all algae and moss deposits.

НАЧИН НА УПОТРЕБА

Stir well before use. Apply with a suitable brush or roller. Dilute the first coat, on an untreated stable substrate, with up to 10% water. Dilute the second coat with up to 5% water. Always spread the paint well and work wet-on-wet to avoid swirl marks. Do not touch up while drying.

УСЛОВИЯ ЗА НАНАСЯНЕ

Do not apply at temperatures below +8°C. Only apply when the temperature of the substrate is at least 3°C above the dew point temperature. Do not apply outdoors under threat of rain, frost or full sun.

НАНАСЯНЕ И РАЗРЕЖДАНЕ: ЧЕТКА

max. 10% water.

НАНАСЯНЕ И РАЗРЕЖДАНЕ: ВАЛЯК

Max. 10% water.

ПОЧИСТВАНЕ НА ОБОРУДВАНЕ И РАЗЛИВИ

Water and soap.

ЗАБЕЛЕЖКИ

The values listed in this technical data sheet are determined on the basis of DIN EN 13300. Always use the necessary personal protective equipment when handling this product. Do not inhale product vapour and spray mist. Always provide adequate ventilation during application. Dispose of residues of this material and its packaging to hazardous or special waste collection point..

СРОК НА ГОДНОСТ

Minimum 12 months in tightly closed original packaging. In tightly closed packaging in a dry, cool and frost-free place.

Дата на издаване: 27/05/2026

Налични цветове и размери на опаковките: Моля, вижте съответната продуктова страница на www.rust-oleum.eu, за да се запознаете с актуалните налични цветове и размери на опаковките.

Отказ от отговорност: Информацията, съдържаща се в този документ, доколкото ни е известно, е вярна и точна и се предоставя добросъвестно, но без гаранция. Счита се, че потребителят се е уверил самостоятелно в пригодността на нашите продукти за неговата/нейната конкретна цел. При никакви обстоятелства Rust-Oleum Europe не носи отговорност за последващи или случайни щети. Продуктите трябва да се съхраняват, обработват и нанасят при условия, съответстващи на препоръките на Rust-Oleum Europe, подробно описани в последното копие на информационния лист на продукта. Отговорност на потребителите е да се уверят, че разполагат с актуалното копие. Последните копия на информационния лист за продукта са на разположение безплатно и могат да бъдат изтеглени от www.rust-oleum.eu или при запитване до нашия отдел за обслужване на клиенти. Rust-Oleum Europe си запазва правото да променя свойствата на своите продукти без предварително уведомление.

Rust-Oleum Netherlands B.V.
Europalaan 9
5232 BC 's-Hertogenbosch
The Netherlands
T: +31 (0) 165 593 636
F: +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T: +44 (0)1914 113 146
F: +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chêne
95322 Herblay
France
T: +33(0) 130 40 00 44
F: +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Belgium
T: +32 (0) 13 460 200
F: +32 (0) 13 460 201
info@rust-oleum.eu

