

SPS



MAT PU-A SPRAY

Sprayable matt paint based on PU-acrylate

- Scratch- and impact resistant
- Skin oils resistant
- Airless and airmix sprayable
- Great freedom of layer thickness
- Very smooth result

MAT PU-A SPRAY

DESCRIPTION

Spray system-compatible, water-based matt paint based on PU-acrylate. Also ideal for application by brush in hard-to-reach areas, such as the rebate sides of tilt and turn windows. Ideal for new builds, maintenance and renovation. Good viscosity, good colour retention, perfect flow properties, creates a washable finish that is resistant to the skin's oils. For interior use.

TECHNICAL DATA

Density (g/cm³): 1.2
Gloss level at 60°: 5-10%
Solids content in volume: 35%

DRY TIMES BY 20° C/RV 50%

Touch dry: 1 hour
Dry to recoat: 6 hours

THEORETICAL CONSUMPTION

Ca. 6 m² / liter per coat

APPLICATION & THINNING: AIRLESS SPRAY

Nozzle opening: 0.009" – 0.012"
Pressure: Ca. 70 bar
Air pressure: -

APPLICATION & THINNING: AIR-ATOMISED SPRAY

Nozzle opening: 0.009" – 0.012"
Pressure: Ca. 60 bar
Air pressure: 1-3 bar

SAFETY DATA

VOC level: 30 g/l
VOC limit: 130 g/l

PH

9.0000

Date issued: 29/06/2022

Available colours & pack sizes: Please refer to the respective product page on www.rust-oleum.eu for an overview of actual available colours and pack sizes.

Disclaimer: The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Rust-Oleum Europe be liable for consequential or incidental damages. Products must be stored, handled, and applied under conditions complying with Rust-Oleum Europe recommendations detailed within the latest copy of the product data sheet. It is the users responsibility to ensure that they have the current copy. Latest copies of the product data sheet is available for free and downloadable from www.rust-oleum.eu or upon a request to our Customer Services department. Rust-Oleum Europe reserves the right to change the properties of its' products without prior notification.

Rust-Oleum Netherlands B.V.
Zilverenberg 16
5234 GM 's-Hertogenbosch
The Netherlands
T : +31 (0) 165 593 636
F : +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T : +44 (0)1914 113 146
F : +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chêne
95322 Herblay
France
T : +33(0) 130 40 00 44
F : +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Belgium
T : +32 (0) 13 460 200
F : +32 (0) 13 460 201
info@rust-oleum.eu



WWW.SPSBV.COM