



# SPS



## PROJECTTEX 2020 MAT

# Ready mixed black project-wallpaint



- Deep black color
- For ceilings and walls
- Universally applicable

# PROJECTTEX 2020 MAT

## DESCRIPTION

Well-covering wall paint for painting large new construction and renovation projects. Suitable for interior and exterior walls, and also ideal for giving ceilings in commercial buildings an industrial look.

## RECOMMENDED USE

Ideal for use on building projects. Designed specifically for painting walls and ceilings in large-scale new-build and renovation projects. Suitable surfaces include: existing wall paint, cement and plaster, concrete, brick, etc.

## RECOMMENDED SYSTEM

**New untreated substrates**- Thoroughly pre-treat highly absorbent substrates with SPS Fix Primer - Thoroughly clean powdery substrates. Pre-treat with SPS Fix-Primer after drying. - Paint over with opaque film after drying. **Existing intact wall paint layers**- Thoroughly clean - Paint over with opaque film after drying. **Existing non-load-bearing wall paint layers**- Remove loose particles - Wash off powdery layers thoroughly and allow to dry - Carry out repairs if necessary. - Pre-treat with SPS Fix-Primer - Once dry, paint over the entire surface. **Contamination by nicotine, moisture, rust or soot** Thoroughly clean - Treat the surface/contamination with SPS Iso-Primer - Once dry, paint over the entire surface. The above systems are general descriptions for most common substrates. For specific applications and/or detailed advice, please contact SPS bv.

## TECHNICAL DATA

Density (g/cm<sup>3</sup>): 1,50  
Gloss level at 85°: 7%, mat.  
Solids content in volume: 45%

## DRY TIMES BY 20° C/RH 50%

Touch dry: 2 hours.  
Dry to recoat: 4 - 6 hours.

## RECOMMENDED WET FILM THICKNESS

Approx. 146 micrometers.

## RECOMMENDED DRY FILM THICKNESS

Approx. 64 micrometers.

## THEORETICAL CONSUMPTION

Approx. 7 m<sup>2</sup> / l per coat

## PRACTICAL CONSUMPTION

Actual consumption depends on the nature and structure of the substrate and the processing method.

## SURFACE PREPARATION

The substrate must be load-bearing, fully bonded, clean, dry, dust- and grease-free. Repair cracks and fissures. Remove and/or repair loose and unstable layers. For exterior use, remove all algae and moss deposits.

## DIRECTIONS FOR USE

Stir well before use. If necessary, dilute the first coat with up to 10% water. Apply with a suitable brush, roller or sprayer. Always work wet-on-wet to avoid deposits. Re-roll all webs in the same direction. Do not touch up while drying.

## APPLICATION CONDITIONS

Do not apply at temperatures below +8°C. Only apply when the temperature of the substrate is at least 3°C above the dew point temperature. Do not apply outdoors under threat of rain, frost or full sun.

## APPLICATION & THINNING: BRUSH

Maximum 10% water.

## APPLICATION & THINNING: ROLLER

Maximum 10% water.

## APPLICATION & THINNING: AIRLESS SPRAY

Airless Nozzle: 0.015"-0.019", Pressure: approx.200 bar, Dilute: Maximum 5% water.  
Airmix Nozzle: 0.017-0.019", Pressure: approx.160 bar, Air pressure: approx. 1.5 bar, Dilute: Maximum 5% water.

The specified settings for spraying this product apply as a starting point. Depending on site conditions, settings will have to be determined by the applicator.

## CLEANING OF EQUIPMENT / SPILLS

Water and soap.

## REMARKS

The values listed in this technical data sheet are determined on the basis of DIN EN 13300. Always use the necessary personal protective equipment when handling this product. Do not inhale product vapour and spray mist. Always provide adequate ventilation during application. Dispose of residues of this material and its packaging to hazardous or special waste collection point.

## SHELF LIFE

Minimum 12 months in tightly closed original container in dry, cool, frost-free place.

Date issued: 27/05/2026

**Available colours & pack sizes:** Please refer to the respective product page on [www.rust-oleum.eu](http://www.rust-oleum.eu) for an overview of actual available colours and pack sizes.

**Disclaimer:** The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Rust-Oleum Europe be liable for consequential or incidental damages. Products must be stored, handled, and applied under conditions complying with Rust-Oleum Europe recommendations detailed within the latest copy of the product data sheet. It is the users responsibility to ensure that they have the current copy. Latest copies of the product data sheet is available for free and downloadable from [www.rust-oleum.eu](http://www.rust-oleum.eu) or upon a request to our Customer Services department. Rust-Oleum Europe reserves the right to change the properties of its' products without prior notification.

**Rust-Oleum Netherlands B.V.**  
Europalaan 9  
5232 BC 's-Hertogenbosch  
The Netherlands  
T: +31 (0) 165 593 636  
F: +31 (0) 165 593 600  
info@rust-oleum.eu

**Tor Coatings Ltd (Rust-Oleum Industrial)**  
Shadon Way, Portobello Ind. Estate  
Birtley, Chester-le-Street  
DH3 2RE United Kingdom  
T: +44 (0)1914 113 146  
F: +44 (0)1914 113 147  
info@rust-oleum.eu

**Rust-Oleum France S.A.S.**  
38, av. du Gros Chêne  
95322 Herblay  
France  
T: +33(0) 130 40 00 44  
F: +33(0) 130 40 99 80  
info@rust-oleum.eu

**N.V. Martin Mathys S.A.**  
Kolenbergstraat 23  
3545 Zelem  
Belgium  
T: +32 (0) 13 460 200  
F: +32 (0) 13 460 201  
info@rust-oleum.eu

