

SPS



PUTZ-GRUND

quartz grain primer for decorative plaster

- Ensures optimal adhesion of the finishing coat
- Good coverage, easy to apply
- Reduces the absorbency of the substrate
- Penetrates the substrate well
- Eliminates colour differences - Breathable, alkali and weather-resistant

PUTZ-GRUND

ОПИСАНИЕ

High-quality, quartz-containing primer for all SPS decorative plasters, based on 100% pure acrylate. Due to its good penetration capacity, this product reduces the suction of the substrate. SPS Putz-Grund also ensures optimal adhesion of the finishing coat. Weather and alkali resistant. For interior and exterior use.

ПРЕПОРЪЧИТЕЛНА УПОТРЕБА

As a primer for decorative plaster finishes. Suitable substrates include all stable, smooth and even surfaces such as: cement and plaster, concrete, plasterboard, old paint layers, etc.

ПРЕПОРЪЧИТЕЛНА СИСТЕМА

New untreated substrates - Thoroughly clean lightly powdering substrates. After drying pretreat with SPS Putz-Grund. - Pre-treat absorbing substrates with SPS Putz-Grund. - Finish with an SPS ornamental plaster. **Existing load-bearing substrates** - Clean the substrate - Smooth and level (structured) substrates with, for instance, SPS Stuc-Finish. - After curing, pretreat with SPS Putz-Grund. - After drying, finish with an SPS ornamental plaster. **Existing non-load-bearing substrates** - Thoroughly remove loose layers. - Wash off powdery layers thoroughly and allow to dry - Carry out any necessary repairs - Pre-treat with SPS Fix-Primer - Smooth and level (structured) substrates - Smooth and level **contaminations caused by nicotine, moisture, rust or soot** Thoroughly clean - Treat the surface/contamination with SPS Iso-Primer - Pre-treat with SPS Putz-Grund - Finish with an SPS decorative plaster. The above systems are general descriptions for the most common substrates. For specific applications and/or detailed advice, please contact SPS bv.

ВРЕМЕ ЗА СУШЕНЕ ДО 20° C/RH 50%

Сух на допир: 2 hours.
Готов за повторно нанасяне: 18 hours.

РАЗХОДНА НОРМА

4 - 5 m²/litre per coat.

КОНСУМАЦИЯ

Actual consumption depends on the nature and structure of the substrate and the processing method.

ПОДГОТОВКА НА ПОВЪРХНОСТТА

The substrate must be smooth, flat, load-bearing, fully bonded, clean, dry, dust- and grease-free. Repair cracks and fissures. Remove and/or repair loose and unstable layers. For exterior use, remove all algae and moss growth.

НАЧИН НА УПОТРЕБА

Stir well before use. Stir regularly during application. Dilute SPS Putz-Grund with up to 20 % pure water, depending on the substrate. For outdoor applications do not dilute. Apply evenly in one coat with a block brush or paint roller.

УСЛОВИЯ ЗА НАНАСЯНЕ

Do not apply at temperatures below +8°C. Only apply when the temperature of the substrate is at least 3°C above the dew point temperature. Do not apply outdoors under threat of rain, frost, or in full sunlight.

НАНАСЯНЕ И РАЗРЕЖДАНЕ: ЧЕТКА

Maximum 20% water.

НАНАСЯНЕ И РАЗРЕЖДАНЕ: ВАЛЯК

Maximum 20% water.

ПОЧИСТВАНЕ НА ОБОРУДВАНЕ И РАЗЛИВИ

Water and soap.

ЗАБЕЛЕЖКИ

Refer to the Surface Assessment Criteria for exterior plastering and the Surface Assessment Criteria for interior plastering to determine whether the substrate is sufficiently smooth and flat to finish with an SPS decorative plaster.

СРОК НА ГОДНОСТ

At least 12 months in tightly closed original packaging in a dry, cool, and frost-free place. Dispose of residues at the chemical waste collection service.

Дата на издаване: 27/05/2026

Налични цветове и размери на опаковките: Моля, вижте съответната продуктова страница на www.rust-oleum.eu, за да се запознаете с актуалните налични цветове и размери на опаковките.

Отказ от отговорност: Информацията, съдържаща се в този документ, доколкото ни е известно, е вярна и точна и се предоставя добросъвестно, но без гаранция. Счита се, че потребителят се е уверил самостоятелно в пригодността на нашите продукти за неговата/нейната конкретна цел. При никакви обстоятелства Rust-Oleum Europe не носи отговорност за последващи или случайни щети. Продуктите трябва да се съхраняват, обработват и нанасят при условия, съответстващи на препоръките на Rust-Oleum Europe, подробно описани в последното копие на информационния лист на продукта. Отговорност на потребителите е да се уверят, че разполагат с актуалното копие. Последните копия на информационния лист за продукта са на разположение безплатно и могат да бъдат изтеглени от www.rust-oleum.eu или при запитване до нашия отдел за обслужване на клиенти. Rust-Oleum Europe си запазва правото да променя свойствата на своите продукти без предварително уведомление.

Rust-Oleum Netherlands B.V.
Europalaan 9
5232 BC 's-Hertogenbosch
The Netherlands
T: +31 (0) 165 593 636
F: +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T: +44 (0)1914 113 146
F: +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chêne
95322 Herblay
France
T: +33(0) 130 40 00 44
F: +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Belgium
T: +32 (0) 13 460 200
F: +32 (0) 13 460 201
info@rust-oleum.eu

