

SPS



QUICK-PRIMER

Primer based on modified alkyd resin

- Quick drying and quickly repaintable
- Good hiding power and filling performance
- Good edge coverage
- Moisture regulating
- Good flow

QUICK-PRIMER

ОПИСАНИЕ

Quick drying, moisture regulating primer with good filling performance. Suitable as a primer on wood, panelling and pre-treated metal. Due to the rapid drying, it is possible to apply two coats in 1 day. Use in combination with SPS top coat paints for maximum durability. For exterior use.

ПРЕПОРЪЧИТЕЛНА УПОТРЕБА

As a primer on untreated wood or wood that has been exposed by sanding in a time-critical situation, for example during maintenance, when a top coat needs to be applied on the same days. In addition, SPS Quick drying primer can be applied down to a temperature of approximately 0°C. Note that the drying time is longer at lower temperatures. SPS Quick drying primer has a shelf life of a few months after opening and can be applied to wood that contains a maximum of 20% moisture.

ПРЕПОРЪЧИТЕЛНА СИСТЕМА

General: The surface must be capable of supporting the paint, clean, dry and free of dust or grease. Slightly round off sharp edges to obtain good edge coverage.

Exposed/untreated wood

- Prime untreated wood using SPS Quick drying primer.
- Allow to dry, lightly sand and remove dust.
- Apply top coat paint.

Existing old coats

- Remove old loose coats.
- Clean the entire surface using SPS Paint cleaner.
- Sand decayed wood down to healthy wood before applying primer.
- Carry out any repairs and apply primer.
- Allow to dry, sand and remove dust.
- Prime exposed parts using SPS Quick drying primer.
- Allow to dry, lightly sand and remove dust.
- Apply top coat paint.

Existing intact coats of paint

- Clean the intact coats using SPS Paint cleaner
- Sand the surface well.
- Add additional primer or another coat of primer using SPS Quick drying primer.
- Allow to dry, lightly sand and remove dust.
- Apply top coat paint.

The systems described above apply for the most common types of surface. For specific applications and/or detailed advice, please contact SPS bv.

ТЕХНИЧЕСКИ ДАННИ

Плътност (г/см ³):	1.65
Съдържание на сухо вещество (по обем):	65%

ВРЕМЕ ЗА СУШЕНЕ ДО 20° C/RH 50%

Сух на допир:	2 hours
Готов за повторно нанасяне:	5 hours

МОКЪР СЛОЙ

62 µm

СУХ СЛОЙ

40 µm

РАЗХОДНА НОРМА

Approx. 16 m²/litre per coat

КОНСУМАЦИЯ

The actual coverage depends on the nature and the structure of the surface and the application method.

ПОДГОТОВКА НА ПОВЪРХНОСТТА

The substrate must be load-bearing, clean, dry, dust- and grease-free. For good edge coverage, slightly round off sharp corners.

НАЧИН НА УПОТРЕБА

Stir well before use. Apply in 1 or more coats using a suitable brush or paint roller. Always work wet-on-wet to prevent marks in the paint. Do not touch up when drying.

УСЛОВИЯ ЗА НАНАСЯНЕ

Do not use at temperatures lower than +8°C. Only apply if the surface temperature is at least 3°C above the dew point temperature. Do not apply outdoors when it is likely to rain, when frost is expected or in direct sunlight. Always use the required personal protective equipment when applying this product. Always ventilate appropriately when applying. Products based on alkyd resins tend to yellow in a dark environment or when covered. In an environment where they are exposed to daylight, this tendency to yellow is much reduced.

НАНАСЯНЕ И РАЗРЕЖДАНЕ: ЧЕТКА

Ready-to-use.

НАНАСЯНЕ И РАЗРЕЖДАНЕ: ВАЛЯК

Ready-to-use.

ПОЧИСТВАНЕ НА ОБОРУДВАНЕ И РАЗЛИВИ

White spirit or brush cleaner

ЗАБЕЛЕЖКИ

Variations in coating thickness, temperature, humidity, etc. affect the drying time.

СРОК НА ГОДНОСТ

Minimum of 12 months in the tightly sealed original packaging in a dry, cool and frost-free place.

Дата на издаване: 27/05/2026

Налични цветове и размери на опаковките: Моля, вижте съответната продуктова страница на www.rust-oleum.eu, за да се запознаете с актуалните налични цветове и размери на опаковките.

Отказ от отговорност: Информацията, съдържаща се в този документ, доколкото ни е известно, е вярна и точна и се предоставя добросъвестно, но без гаранция. Счита се, че потребителят се е уверил самостоятелно в пригодността на нашите продукти за неговата/нейната конкретна цел. При никакви обстоятелства Rust-Oleum Europe не носи отговорност за последващи или случайни щети. Продуктите трябва да се съхраняват, обработват и нанасят при условия, съответстващи на препоръките на Rust-Oleum Europe, подробно описани в последното копие на информационния лист на продукта. Отговорност на потребителите е да се уверят, че разполагат с актуалното копие. Последните копия на информационния лист за продукта са на разположение безплатно и могат да бъдат изтеглени от www.rust-oleum.eu или при запитване до нашия отдел за обслужване на клиенти. Rust-Oleum Europe си запазва правото да променя свойствата на своите продукти без предварително уведомление.

Rust-Oleum Netherlands B.V.
Europalaan 9
5232 BC 's-Hertogenbosch
The Netherlands
T: +31 (0) 165 593 636
F: +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T: +44 (0)1914 113 146
F: +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chêne
95322 Herblay
France
T: +33(0) 130 40 00 44
F: +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Belgium
T: +32 (0) 13 460 200
F: +32 (0) 13 460 201
info@rust-oleum.eu

