

# SPS



## RESIMAT PLUS

### Optimally cleanable, extra matt acrylic wall paint

- Remains matt after cleaning
- No white marking
- Optimally cleanable
- Extra matt
- Scrub-resistant, class 1

# RESIMAT PLUS

## DESCRIPTION

The dry paint coating is moisture-repellent to reduce dirt build-up and permanently matt after cleaning. Highly suitable for use on walls in public buildings and rooms that are prone to dirt/dust accumulation such as kitchens and entrance halls. For interior use.

## RECOMMENDED USE

as a durable and very easily cleanable, even matt finish for interior walls and ceilings. Suitable surfaces include: existing coats of wall paint, cement and plasterwork, concrete, brick, gypsum panelling, etc. Also extremely suitable for painting glass fibre fabric.

## RECOMMENDED SYSTEM

**New, untreated substrates** - Prime very absorbent substrates completely with SPS Fix primer. - Clean powdery substrates thoroughly. Pre-treat with SPS Fix Primer after drying. - After drying and depending on colour, paint with SPS Resimat Plus in two opaque coats. **Existing intact wall paint layers** - Thoroughly clean - If necessary apply an intermediate coat of SPS Wall-Primer Plus. - After drying and depending on colour, apply 2 opaque coats of SPS Resimat Plus. **Existing non-bearing wall paint layers**- Remove loose particles. - Thoroughly wash off any powdering layers and allow to dry. - Carry out any necessary repairs. - Pre-treat with SPS Fix primer. - After drying and depending on colour, paint in 2 coats with SPS Resimat Plus. **Contamination by nicotine, moisture, rust or soot** - Clean thoroughly. - Treat the surface/contamination with SPS Iso-Primer Plus. - After drying and depending on colour, paint off in 2 coats with SPS Resimat Plus. The systems mentioned are general descriptions for most common substrates. For specific applications and/or detailed advice, please contact SPS bv.

## TECHNICAL DATA

Density (g/cm <sup>3</sup> ):	1,51
Gloss Level:	Extra-Matt
Gloss level at 85°:	1%
Solids Content in weight:	61,1
Solids content in volume:	40,9

## DRY TIMES BY 20° C/RH 50%

Touch dry:	2 hours.
Dry to recoat:	4 - 6 hours.
Fully cured:	Approx 28 days.

## RECOMMENDED WET FILM THICKNESS

Approx. 123 micrometres

## RECOMMENDED DRY FILM THICKNESS

Approx. 53 micrometres

## THEORETICAL CONSUMPTION

Approx. 8 m<sup>2</sup>/litre per coat

## PRACTICAL CONSUMPTION

Actual consumption depends on the suction and structure of the substrate and the application method.

## SURFACE PREPARATION

The substrate must be load-bearing, fully bonded, clean, dry, dust- and grease-free. Repair cracks and fissures. Remove and/or repair loose and unstable layers.

## DIRECTIONS FOR USE

Stir well before use. Apply in 1 or 2 layers, with a suitable brush or roller (for best results use a microfibre roller) For optimum end results, apply in at least 2 layers. To avoid deposits, always work wet-on-wet. Re-roll all webs in the same direction. Do not touch up during drying.

## APPLICATION CONDITIONS

Do not apply at temperatures below +8°C. Only apply when the temperature of the substrate is at least 3°C above the dew point temperature.

## APPLICATION & THINNING: BRUSH

Maximum 5% water.

## APPLICATION & THINNING: ROLLER

Maximum 5% water.

## APPLICATION & THINNING: AIRLESS SPRAY

Airless: Nozzle: 0.017-0.021", Pressure: approx.180 bar, Dilute: max. 5% water.

Airmix: Nozzle: 0.015-0.019", Pressure: approx. 125 bar, Air pressure: approx. 1.5 bar, Dilute: max. 5% water.

Spraying is only recommended for white/ base P and colours from this base paint. The specified settings for spraying this product apply as a starting point. Depending on site conditions, settings will have to be determined by the applicator.

## CLEANING OF EQUIPMENT / SPILLS

Water and soap.

Date issued: 27/05/2026

**Available colours & pack sizes:** Please refer to the respective product page on [www.rust-oleum.eu](http://www.rust-oleum.eu) for an overview of actual available colours and pack sizes.

**Disclaimer:** The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Rust-Oleum Europe be liable for consequential or incidental damages. Products must be stored, handled, and applied under conditions complying with Rust-Oleum Europe recommendations detailed within the latest copy of the product data sheet. It is the users responsibility to ensure that they have the current copy. Latest copies of the product data sheet is available for free and downloadable from [www.rust-oleum.eu](http://www.rust-oleum.eu) or upon a request to our Customer Services department. Rust-Oleum Europe reserves the right to change the properties of its' products without prior notification.

**Rust-Oleum Netherlands B.V.**  
Europalaan 9  
5232 BC 's-Hertogenbosch  
The Netherlands  
T: +31 (0) 165 593 636  
F: +31 (0) 165 593 600  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)

**Tor Coatings Ltd (Rust-Oleum Industrial)**  
Shadon Way, Portobello Ind. Estate  
Birtley, Chester-le-Street  
DH3 2RE United Kingdom  
T: +44 (0)1914 113 146  
F: +44 (0)1914 113 147  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)

**Rust-Oleum France S.A.S.**  
38, av. du Gros Chêne  
95322 Herblay  
France  
T: +33(0) 130 40 00 44  
F: +33(0) 130 40 99 80  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)

**N.V. Martin Mathys S.A.**  
Kolenbergstraat 23  
3545 Zelem  
Belgium  
T: +32 (0) 13 460 200  
F: +32 (0) 13 460 201  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)



# RESIMAT PLUS

## REMARKS

The values listed in this technical data sheet are determined on the basis of DIN EN 13300. Always use the necessary personal protective equipment when handling this product. Do not inhale product vapour and spray mist. Always ventilate appropriately during processing. Dispose of residues and packaging to hazardous or special waste collection point.

Optimum cleanability is achieved after complete curing for 30 days. Most common contaminants are easily and well removed with plenty of clean, lukewarm water, possibly with a mild soap or detergent. Use a clean non-abrasive sponge and allow the surface to dry through evaporation of the water. It is possible to wash the surface with sufficient lukewarm water to remove soap residues, let the surface dry through evaporation of the water.

When drying this product, slight (gloss) bumps and striping, caused by insufficient paint distribution, should disappear. If this is not the case, an additional coat should be applied. Variations in layer thickness, temperature, humidity, etc. will affect drying time, gloss level and flow.

With dark colours, roller tracks are more likely to appear due to the absorption of light, highlighting defects in the surface. To avoid this, best prefer spray application.

## SHELF LIFE

Minimum of 12 months in the tightly sealed original packaging in a dry, cool and frost-free place.

Date issued: 27/05/2026

**Available colours & pack sizes:** Please refer to the respective product page on [www.rust-oleum.eu](http://www.rust-oleum.eu) for an overview of actual available colours and pack sizes.

**Disclaimer:** The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Rust-Oleum Europe be liable for consequential or incidental damages. Products must be stored, handled, and applied under conditions complying with Rust-Oleum Europe recommendations detailed within the latest copy of the product data sheet. It is the users responsibility to ensure that they have the current copy. Latest copies of the product data sheet is available for free and downloadable from [www.rust-oleum.eu](http://www.rust-oleum.eu) or upon a request to our Customer Services department. Rust-Oleum Europe reserves the right to change the properties of its' products without prior notification.

**Rust-Oleum Netherlands B.V.**  
Europalaan 9  
5232 BC 's-Hertogenbosch  
The Netherlands  
T: +31 (0) 165 593 636  
F: +31 (0) 165 593 600  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)

**Tor Coatings Ltd (Rust-Oleum Industrial)**  
Shadon Way, Portobello Ind. Estate  
Birtley, Chester-le-Street  
DH3 2RE United Kingdom  
T: +44 (0)1914 113 146  
F: +44 (0)1914 113 147  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)

**Rust-Oleum France S.A.S.**  
38, av. du Gros Chêne  
95322 Herblay  
France  
T: +33(0) 130 40 00 44  
F: +33(0) 130 40 99 80  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)

**N.V. Martin Mathys S.A.**  
Kolenbergstraat 23  
3545 Zelem  
Belgium  
T: +32 (0) 13 460 200  
F: +32 (0) 13 460 201  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)

