

SPS



UNITEX 4040 MAT

Universally applicable high-quality wall paint

- Excellent coverage
- Highly weather-resistant
- Scrub-resistant
- Matt
- Breathable

UNITEX 4040 MAT

DESCRIPTION

Universally applicable, matt, high quality wall paint with excellent hiding power based on a synthetic resin dispersion. High coverage and good flow. For interior and exterior applications, also for damp rooms. Breathable, highly weather-resistant and scrub-resistant. For interior and exterior use.

RECOMMENDED USE

Intended for durable finishing of exterior walls and interior walls, also in damp areas. Suitable substrates include: existing wall paint layers, cement and plaster, concrete, brick, gypsum board, etc. Also suitable for painting glass fabric.

RECOMMENDED SYSTEM

New, untreated substrates- Thoroughly pre-treat highly absorbent substrates with SPS Fix Primer - Thoroughly clean powdery substrates. After drying pretreat with SPS Fix-Primer. - After drying apply opaque top coat. **Existing intact wall paint layers**- Thoroughly clean - If necessary apply an intermediate coat of thinned SPS Unitex 4040. - After drying apply opaque top coat. **Existing non-bearing wall paint layers**- Remove loose particles - Thoroughly wash off any powders and allow to dry. - Make any necessary repairs - Pre-treat with SPS Fix-Primer - Once dry, paint over the surface in a opaque manner. **Contamination by nicotine, moisture, rust or soot** Thoroughly clean - Treat the surface/contamination with SPS Iso-Primer - Once dry, paint over the surface in a opaque manner. The systems mentioned are general descriptions for most common substrates. For specific applications and/or detailed advice, please contact SPS bv.

TECHNICAL DATA

Density (g/cm ³):	1,48
Gloss Level:	Matt
Gloss level at 85°:	<10%, Matt
Solids content in volume:	40%

DRY TIMES BY 20° C/RH 50%

Touch dry:	2 hours.
Dry to recoat:	4 - 6 hours.

RECOMMENDED WET FILM THICKNESS

Approx. 125 micrometers

RECOMMENDED DRY FILM THICKNESS

Approx. 50 micrometers

THEORETICAL CONSUMPTION

Approx. 8 m² / ltr. per coat. The stated yield is theoretical.

PRACTICAL CONSUMPTION

Actual consumption depends on the nature and structure of the substrate and the processing method.

SURFACE PREPARATION

The substrate must be load-bearing, fully bonded, clean, dry, dust- and grease-free. Repair cracks and fissures. Remove and/or repair loose and unstable layers. For exterior use, remove all algae and moss deposits.

DIRECTIONS FOR USE

Stir well before use. If necessary, dilute the first coat with up to 10% water. Apply with a suitable brush, roller or sprayer. Always work wet-on-wet to avoid deposits. Re-roll all surfaces in the same direction. Do not touch up while drying.

APPLICATION CONDITIONS

Do not process at temperatures below+8°C. Apply only when the temperature of the substrate is at least 3°C above the dew point temperature. Do not apply outdoors under threat of rain, frost, or in full sunlight.

APPLICATION & THINNING: BRUSH

Maximum 10% water.

APPLICATION & THINNING: ROLLER

Maximum 10% water.

APPLICATION & THINNING: AIRLESS SPRAY

Airless: Nozzle opening: 0.017-0.019", Pressure: approx. 200 bar, Dilute: Maximum 10% water.

Airmix: Nozzle opening: 0.017-0.019", Pressure: >80 bar, Air pressure: approx. 1.5 bar, Dilute: Maximum 10% water.

The specified settings for spraying this product are a starting point. Depending on site conditions, settings will have to be determined by the applicator.

CLEANING OF EQUIPMENT / SPILLS

Water and soap

REMARKS

The values listed in this technical data sheet are determined on the basis of DIN EN 13300. Always use the necessary personal protective equipment when handling this product. Do not inhale product vapor and spray mist. Always ventilate appropriately during processing. Take residues of this substance and packaging to hazardous or special waste collection point. With (dark-colored) matt wall paints, after the first rain shower clearly visible gloss traces may appear, also called snail marks. These are admixtures and contents that exit from the still fresh paint layer. These are then visible as yellowish, transparent, slightly shiny and sticky streaks. These contents are water soluble and will usually be washed away after a few rain showers. If necessary, rinsing with clean water can expedite the cleaning of the facade. Natural washing out is preferred. The paint layer will then regain an even color, the gloss streaks will fade and disappear. This phenomenon does not otherwise affect the quality of the paint layer.

SHELF LIFE

Minimum 12 months in tightly closed original container in dry, cool, and frost-free place.

Date issued: 27/05/2026

Available colours & pack sizes: Please refer to the respective product page on www.rust-oleum.eu for an overview of actual available colours and pack sizes.

Disclaimer: The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Rust-Oleum Europe be liable for consequential or incidental damages. Products must be stored, handled, and applied under conditions complying with Rust-Oleum Europe recommendations detailed within the latest copy of the product data sheet. It is the users responsibility to ensure that they have the current copy. Latest copies of the product data sheet is available for free and downloadable from www.rust-oleum.eu or upon a request to our Customer Services department. Rust-Oleum Europe reserves the right to change the properties of its' products without prior notification.

Rust-Oleum Netherlands B.V.
Europalaan 9
5232 BC 's-Hertogenbosch
The Netherlands
T : +31 (0) 165 593 636
F : +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T : +44 (0)1914 113 146
F : +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chêne
95322 Herblay
France
T : +33(0) 130 40 00 44
F : +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Belgium
T : +32 (0) 13 460 200
F : +32 (0) 13 460 201
info@rust-oleum.eu

