

#### Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

Date of issue: 4-8-2016 Revision date: 4-8-2016 Supersedes: 22-1-2014 Version: 1.1

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture

Product name : Finess Bielzenzwart (Sleeper black)

[UNOFFICIAL DOCUMENT]

Product code : 15041060100
Product group : Trade product

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### 1.2.1. Relevant identified uses

Intended for general public

Main use category : Consumer uses, Professional use, Industrial use

Use of the substance/mixture : Consumer uses: Private households (= general public = consumers)

Paint

#### 1.2.2. Uses advised against

No additional information available

#### 1.3. Details of the supplier of the safety data sheet

**Supplier** S.P.S. BV Zilverenberg 16

5234 GM 's-Hertogenbosch. - Nederland. T +31 (0)73 642 27 10 - F +31 (0)73 642 60 95

info@spsbv.com - www.spsbv.com

Responsible formatting SDS Mantech Nederland B.V.

Kobaltweg 7

5234 GN 's-Hertogenbosch - Nederland T +31 (0)73 70 70 112 - F +31 (0)73 64 43 861

info@mantechbv.nl - www.mantechbv.nl

#### 1.4. Emergency telephone number

Emergency number : SPS BV.: +31 73 642 27 10 [7:30 - 16:30]

NL - Nationaal Vergiftigingen Informatie Centrum (NVIC) Emergency telephone (24 hours): +31 30 274 88 88 (Only for doctors to inform accidental poisoning)

## **SECTION 2: Hazards identification**

#### 2.1. Classification of the substance or mixture

#### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable liquids, Category 3

Specific target organ toxicity — Single exposure, Category 3, Narcosis

Specific target organ toxicity — Repeated exposure, Category 1

H372

Aspiration hazard, Category 1

H304

Hazardous to the aquatic environment — Chronic Hazard, Category 2

H411

Full text of hazard classes and H-statements : see section 16

#### Adverse physicochemical, human health and environmental effects

Classified as dangerous according to the criteria of Regulation (EC) No 1272/2008.

#### 2.2. Label elements

#### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)









GHS

GHS09

Signal word (CLP) : Danger

Hazardous ingredients : Naphtha (petroleum), hydrodesulfurized heavy

13-9-2016 EN (English) SDS Ref.: AKP04100 1/9

### Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

Hazard statements (CLP) H226 - Flammable liquid and vapour

H304 - May be fatal if swallowed and enters airways

H336 - May cause drowsiness or dizziness

H372 - Causes damage to organs (central nervous system) through prolonged or repeated

exposure (if inhaled)

H411 - Toxic to aquatic life with long lasting effects

P314 - Get medical advice/attention if you feel unwell Precautionary statements (CLP)

P260 - Do not breathe vapours

P370+P378 - In case of fire: Use carbon dioxide (CO2), foam, extinguishing powder, Water fog

for extinction

P210 - Keep away from heat, sparks, open flames, hot surfaces. - No smoking

P270 - Do not eat, drink or smoke when using this product P271 - Use only outdoors or in a well-ventilated area

P273 - Avoid release to the environment

P331 - Do NOT induce vomiting

P391 - Collect spillage

P403+P233 - Store in a well-ventilated place. Keep container tightly closed

P405 - Store locked up

P501 - Dispose of contents/container to hazardous or special waste collection point, in

accordance with local, regional, national and/or international regulation P101 - If medical advice is needed, have product container or label at hand

P102 - Keep out of reach of children

P301+P310 - IF SWALLOWED: immediately call a POISON CENTER or doctor/physician

[ Spray application; P261 - Avoid breathing spay. ]

EUH066 - Repeated exposure may cause skin dryness or cracking **FUH-statements** 

EUH210 - Safety data sheet available on request

Security closing plug for children : Applicable Tactile warning : Applicable

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

#### **SECTION 3: Composition/information on ingredients**

#### **Substance**

Not applicable

#### 3.2. **Mixture**

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
	(CAS No) 8052-42-4 (EC no) 232-490-9	25 - 50	Not classified
Naphtha (petroleum), hydrodesulfurized heavy	(CAS No) 64742-82-1 (EC no) 265-185-4 (EC index no) 649-330-00-2 (REACH-no) 01-2119458049-33	> 25	Flam. Liq. 3, H226 STOT SE 3, H336 STOT RE 1, H372 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 Skin Irrit. 2, H315

Full text of H-statements: see section 16

#### **SECTION 4: First aid measures**

#### **Description of first aid measures**

First-aid measures general : In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious place in recovery position and seek medical advice.

First-aid measures after inhalation Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, administer artificial respiration. Give nothing by mouth.

First-aid measures after skin contact After contact with skin, take off immediately all contaminated clothing, and wash immediately

with plenty of water and soap. Obtain medical attention if irritation persists.

First-aid measures after eye contact Remove contact lenses, irrigate copiously with clean, fresh water for at least 10 minutes,

holding the eyelids apart and seek medical advice.

13-9-2016 EN (English) SDS Ref.: AKP04100 2/9

#### Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

First-aid measures after ingestion : If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Keep at rest. Do NOT induce vomiting. Take, if necessary 1 or 2 tablespoons laxative (sodium sulphate).

#### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation : May cause respiratory irritation. Symptoms of inhalation include drowsiness, weakness,

headache, dizziness, nausea, vomiting.

Symptoms/injuries after skin contact : Repeated exposure may cause skin dryness or cracking.

Symptoms/injuries after eye contact : May cause moderate irritation, including burning sensation, tearing, redness or swelling.

Symptoms/injuries after ingestion : Ingestion may cause nausea, vomiting and diarrhea. May cause lung damage if swallowed.

Dry/sore throat. High vapour concentration may cause shortness of breath (lung oedema).

#### 4.3. Indication of any immediate medical attention and special treatment needed

Seek medical attention if ill effect or irritation develops. Immediate specific treatment is necessary in case of poisoning.

#### **SECTION 5: Firefighting measures**

#### 5.1. Extinguishing media

Suitable extinguishing media : carbon dioxide (CO2), powder, alcohol-resistant foam, water spray.

Unsuitable extinguishing media : Do not use a heavy water stream.

#### 5.2. Special hazards arising from the substance or mixture

Fire hazard : Fire will produce dense black smoke. Exposure to decomposition products may cause a health

: Cool closed containers exposed to fire with water.

hazard. Appropriate breathing apparatus may be required.

Reactivity in case of fire : Will float and can be reignited on water surface.

Hazardous decomposition products in case of : Thermal decomposition generates : Carbon monoxide.

fire

F.O. A.I. . . .

Precautionary measures fire

5.3. Advice for firefighters

Protection during firefighting : Self contained breathing apparatus. Complete protective clothing.

Other information : Do not allow run-off from fire fighting to enter drains or water courses.

#### **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.1.1. For non-emergency personnel

Protective equipment : Use personal protective equipment as required. Spills of this product present a serious slipping

hazard

Emergency procedures : Do not smoke. Avoid ignition sources. Ventilate area. Do not breathe vapours. Vapours may be

heavier than air. Accumulation in low-lying areas gives chance of suffocation.

#### 6.1.2. For emergency responders

Protective equipment : Equip rescue crew with proper protection. Spills of this product present a serious slipping

hazard.

Emergency procedures : No smoking. Avoid ignition sources. Ventilate area. Do not breathe vapours. Vapours may be

heavier than air. Accumulation in low-lying areas gives chance of suffocation.

#### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if product enters sewers or public waters.

#### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth,

vermiculite, diatomaceous earth and place in container for disposal according to local

regulations (see section 13).

Other information : Clean preferably with a detergent - avoid use of solvents.

#### 6.4. Reference to other sections

See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

#### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Additional hazards when processed : Due to the organic solvents' content of the preparation: Vapours are heavier than air and may

spread along floors. Vapours may form explosive mixtures with air. Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher

than the occupational exposure limits.

13-9-2016 EN (English) SDS Ref.: AKP04100 3/9

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

Precautions for safe handling

Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentrations higher than the occupational exposure limits. In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard. Preparation may charge electrostatically: always use earthing leads when transferring from one container to another. Operators should wear anti-static footwear and clothing and floors should be of the conducting type. Keep container tightly closed. Isolate from sources of heat, sparks and open flame. No sparking tools should be used. Avoid skin and eye contact. Avoid the inhalation of dust, particulates and spray mist arising from the application of this preparation. Avoid inhalation of dust from sanding. For personal protection see Section 8. Never use pressure to empty: container is not a pressure vessel. Always keep in containers of same material as the original one. Comply with the health and safety at work laws. When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits. Materials such as cleaning rags, paper wipes and protective clothing, which are contaminated with the product may spontaneously self-ignite some hours later. To avoid the risks of fires, all contaminated materials should be:

- stored in purpose-built containers or in metal containers with tight-fitting self-closing lids or
- laid out flat in a single layer to dry or
- placed in a closed metal container soaked with water or
- washed out well with warm soapy water before disposal.

Contaminated materials should be removed from the workplace at the end of each working day and be stored outside.

Handling temperature < 35 °C

: Smoking, eating and drinking should be prohibited in application area. Hygiene measures

#### Conditions for safe storage, including any incompatibilities

: Keep container tightly closed and dry. Technical measures

Storage conditions : Observe the label precautions. Store in accordance with local/national regulations.

Storage temperature 5 - 30 °C Store in dry, well-ventilated area. Heat and ignition sources Keep away from heat and direct sunlight.

: Oxidizing agents. Prohibitions on mixed storage

Storage area : Prevent unauthorised access.

: Containers which are opened must be carefully resealed and kept upright to prevent leakage. Special rules on packaging

Packaging materials Keep in original containers.

Specific end use(s)

#### **SECTION 8: Exposure controls/personal protection**

#### **Control parameters**

No additional information available

#### **Exposure controls**

#### Appropriate engineering controls:

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL, suitable respiratory protection must be worn.

#### Personal protective equipment:

Protective goggles. Gloves. In case of inadequate ventilation wear respiratory protection.

#### Hand protection:

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals. The breakthrough time must be greater than the end use time of the product. Nitrile rubber gloves (>0.5 mm, Breakthroughtime BTT: 480 min.). The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed. Gloves should be replaced regularly and if there is any sign of damage to the glove material. Always ensure that gloves are free from defects and that they are stored and used correctly. The performance or effectiveness of the glove may be reduced by physical/ chemical damage and poor maintenance. Barrier creams may help to protect the exposed areas of the skin, they should however not be applied once exposure has occurred

#### Eve protection:

Use safety eyewear designed to protect against splash of liquids

#### Skin and body protection:

13-9-2016 EN (English) SDS Ref.: AKP04100 4/9

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

Cotton or cotton/synthetic overalls or coveralls are normally suitable. Every part of the skin which had contact with the product should have been washed thoroughly

#### Respiratory protection:

If workers are exposed to concentrations above the exposure limit they must use appropriate, certified respirators. Combined gas/dust mask with filter type AX/P2



Flash point





#### **SECTION 9: Physical and chemical properties**

#### Information on basic physical and chemical properties

Physical state : Liquid Colour : Black. Odour : characteristic. Odour threshold : No data available рΗ : Not applicable Relative evaporation rate (butylacetate=1) : No data available Relative evaporation rate (ether=1) : No data available Melting point : No data available : < -20 °C Freezing point Boiling point 160 °C : > 23 °C (PMcc)

Auto-ignition temperature : > 245

Decomposition temperature : When exposed to heat, may decompose liberating hazardous gases

Flammability (solid, gas) : This product is flammable

: No data available Vapour pressure

Relative vapour density at 20 °C

Relative density : No data available Density 0,85 g/ml Solubility : Insoluble. Log Pow No data available

No data available Log Kow No data available Viscosity, kinematic

≤ 7 cP (>15 sec., Cup 4 mm.) Viscosity, dynamic Explosive properties : No dangerous reactions known.

Oxidising properties : Not applicable. Explosive limits : 0,6 - 9 vol %

#### 9.2. Other information

VOC content : (cat.A/f): 700 g/l (2010). This product contains max. 350 g/l VOC.

### **SECTION 10: Stability and reactivity**

### Reactivity

No dangerous reactions known.

#### 10.2. **Chemical stability**

Stable under recommended storage and handling conditions (see section 7).

#### 10.3. Possibility of hazardous reactions

No additional information available

#### **Conditions to avoid**

When exposed to high temperatures may produce hazardous decomposition products.

#### Incompatible materials

See Heading 7.

13-9-2016 EN (English) SDS Ref.: AKP04100

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

#### **Hazardous decomposition products**

Such as carbon monoxide and dioxide, smoke, oxides of nitrogen etc.

#### SECTION 11: Toxicological information

#### Information on toxicological effects

Acute toxicity

: There are no data available on the preparation itself. Classified as dangerous according to the criteria of Regulation (EC) No 1272/2008, See Sections 2 and 3 for details

	criteria of Regulation (EC) No 12/2/2008. See Sections 2 and 3 for details
Finess Bielzenzwart (Sleeper black) [UNOFFICIAL DOCUMENT]	
LD50 oral	4292 mg/l (calculated value)
LD50 dermal	> 2692 mg/kg bodyweight (calculated value)
LC50 inhalation rat (mg/l)	> 10 (calculated value)
ATE CLP (vapours)	5,000 mg/l
Naphtha (petroleum), hydrodesulfurized hea	ıvy (64742-82-1)
LD50 oral rat	> 5000 mg/kg bodyweight
LD50 dermal rabbit	> 3160 mg/kg bodyweight
LC50 inhalation rat (mg/l)	> 12000 mg/m³
Skin corrosion/irritation	<ul> <li>May cause slight irritation. Repeated exposure may cause skin dryness or cracking. Repeated or prolonged contact with the product may lead to removal of natural fats from the skin resulting in non-allergic contact dermatitis and absorption through the skin pH: Not applicable</li> </ul>
Serious eye damage/irritation	: The liquid splashed in the eyes may cause irritation and reversible damage pH: Not applicable
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: May cause drowsiness or dizziness.
Specific target organ toxicity (repeated exposure)	: Causes damage to organs (central nervous system) through prolonged or repeated exposure (if inhaled).

: Not classified. May be fatal if swallowed and enters airways. Aspiration hazard

Potential adverse human health effects and

symptoms

 $: \ \, \text{Exposure to component solvents vapours concentration in excess of the stated occupational} \\$ exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Solvents may cause some of the above effects by absorption through the skin. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

: The mixture has been assessed following the conventional method of the Regulation (EC) No.

#### **SECTION 12: Ecological information**

**Toxicity** 

Ecology - general

	1272/2008 [CLP] and is classified as dangerous for the environment. See Sections 2 and 3 for details.
Ecology - water	<ul> <li>Toxic to aquatic life with long lasting effects. On the surface can form an oil film which may decrease the oxygen with possible adverse effects on aquatic organisms.</li> </ul>
Finess Bielzenzwart (Sleeper black) [UNOFFICIAL DOCUMENT]	
LC50 fish 1	2 mg/l (calculated value)
EC50 Daphnia 1	2 mg/l (calculated value)
Additional information	Data lacking. Dangerous for the environment. 60%.
Naphtha (petroleum), hydrodesulfur	ized heavy (64742-82-1)
LC50 fish 1	1 mg/l
EC50 Daphnia 1	1 mg/l
ErC50 (algae)	2.6 mg/l

13-9-2016 EN (English) SDS Ref.: AKP04100 6/9

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

#### 12.2. Persistence and degradability

Finess Bielzenzwart (Sleeper black) [UNOFFICIAL DOCUMENT]	
Persistence and degradability	There are no data available on the preparation itself. May cause long-term adverse effects in the aquatic environment.

#### 12.3. Bioaccumulative potential

Finess Bielzenzwart (Sleeper black) [UNOFFICIAL DOCUMENT]		
Log Pow	No data available	
Log Kow	No data available	60
Bioaccumulative potential	There are no data available on the preparation itself.	

#### 12.4. Mobility in soil

Finess Bielzenzwart (Sleeper black) [UNOFFICIAL DOCUMENT]	
Ecology - soil	There are no data available on the preparation itself. Absorbed by the soil and has low mobility. Floats on water.

#### 12.5. Results of PBT and vPvB assessment

# Finess Bielzenzwart (Sleeper black) [UNOFFICIAL DOCUMENT]

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII

This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

#### 12.6. Other adverse effects

Additional information : Product may not flow into sewer or superficial water

#### **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

Regional legislation (waste) : Do not allow to enter drains or water courses.

Waste disposal recommendations : Dispose of this material and its container to hazardous or special waste collection point.

Additional information : Uncleaned packaging: Recommendation: Not completely empty packaging must been treated

complying Directive 91/689/EEC.

European List of Waste (LoW) code : 08 00 00 - WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE

(MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES,

SEALANTS AND PRINTING INKS

08 01 11\* - waste paint and varnish containing organic solvents or other dangerous substances

08 01 12 - waste paint and varnish other than those mentioned in 08 01 11

### **SECTION 14: Transport information**

In accordance with ADR / RID / IMDG / IATA / ADN

ADR	IMDG	IATA	ADN	RID
14.1. UN number				
1263	Not applicable	Not applicable	Not applicable	1263
14.2. UN proper shippi	ng name			
PAINT / PAINT RELATED MATERIAL	Not applicable	Not applicable	Not applicable	Not applicable
Transport document descr	iption			
UN 1263 PAINT / PAINT RELATED MATERIAL, 9, III, ENVIRONMENTALLY HAZARDOUS				UN 1263 , 3, ENVIRONMENTALLY HAZARDOUS
14.3. Transport hazard	class(es)			
9	Not applicable	Not applicable	Not applicable	3
	¥2>	¥2>	¥2>	3
14.4. Packing group				
III	Not applicable	Not applicable	Not applicable	Not applicable

13-9-2016 EN (English) SDS Ref.: AKP04100 7/9

#### Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

ADR	IMDG	IATA	ADN	RID
14.5. E	nvironmental hazards			
Dangerous environmen		Dangerous for the environment : Yes		Dangerous for the environment : Yes
		No supplementary inform	ation available	

14.6. Special precautions for user

Special transport precautions : Transport within user's premises: Always transport in closed containers that are upright and

secure. Ensure that persons transporting the product know what to do in the event of an

accident or spillage

- Overland transport

Classification code (ADR) : M6
Transport category (ADR) : 3

- Transport by sea

Transport regulations (IMDG) : Not determined.

- Air transport

Transport regulations (IATA) : Not determined.

- Inland waterway transport

Transport regulations (ADN) : Not determined.

- Rail transport

No data available

#### 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

IBC code: Not applicable.Ship type: Not determined.Pollution category: Not determined.

#### **SECTION 15: Regulatory information**

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

VOC content : (cat.A/f): 700 g/l (2010). This product contains max. 350 g/l VOC.

Other information, restriction and prohibition

regulations

## 15.1.2. National regulations

No additional information available

#### 15.2. Chemical safety assessment

Not applicable

#### **SECTION 16: Other information**

Indication of changes:

1.1 Product code Modified				
	1.	Froduct code	Modified	

#### Full text of H- and EUH-statements:

Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Asp. Tox. 1	Aspiration hazard, Category 1
Flam. Liq. 3	Flammable liquids, Category 3
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT RE 1	Specific target organ toxicity — Repeated exposure, Category 1
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis

13-9-2016 EN (English) SDS Ref.: AKP04100 8/9

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

H304	Flammable liquid and vapour	<b>.</b>
<b>⊔</b> 215	May be fatal if swallowed and enters airways	
H315 H336	Causes skin irritation	
H372	May cause drowsiness or dizziness  Causes damage to organs through prolonge	d or repeated expecure
H411	Toxic to aquatic life with long lasting effects	d of repeated exposure
EUH066	Repeated exposure may cause skin dryness	or cracking
EUH210	Safety data sheet available on request	, or orderling
SDS EU (REACH bijlage II) [ This information is based on our of construed as guaranteeing any sp	current knowledge and is intended to describe the product for the purposes of h	nealth, safety and environmental requirements only. It should not therefore
		OFFOR
	OCI	
JHOFF!		
JAOFF		