

Description: Rust-resistant top coat with hammered effect for metals. Can be applied directly to metal. For interior and exterior use.

Application: Excellent for coating metal objects, but can also be used on wood.

Properties:

- Anti-rust properties
- Water repellent
- Scratch and impact resistant

Colours: Various colours

Handling: Stir thoroughly prior to use. Apply 2 undiluted coats with a brush or paint roller.

Covers: Approx. 10 m²/litre per coat.

Drying time at 23°C and relative humidity of 65%:

Dust-dry after approx. 1 hours.
Can be painted over after approx. 8 hours.
Cures after 7 days.

SYSTEM CONSTRUCTION

Substrate: The surface must be clean, dry and free from dust or grease. Fully remove all rust and loose paint with a steel brush.

Untreated (slightly rusty) metal: Carefully remove grease, any mill scale and rust.

Coated metal in good condition: Degrease, sand lightly and remove any dust.

Coated metal in poor condition: Pre-treat surfaces and any areas of rust pitting with a Finess anti-rust primer .

Wood: Degrease, sand lightly and remove any dust. For the best effect, pre-treat with Finess Primer.

Zinc, aluminium and galvanised steel: Prime with Finess Universal Primer.

TECHNICAL DATA

Binding agent: Urethane modified alkyd resin

Pigments: Rust-preventive lead and chromate-free pigments

Solvent: White spirit

Solid components: 50% by volume

SG: Approx. 1 g/ml

Viscosity: Krebs Stormer 90-100 KU @ +20°C

Fineness: 10-25 microns

Recommended coat thickness: 40 microns dry, 80 microns wet

Degree of gloss: Glossy

Tint: Various colours

Flash point: 39°C

Hazard classification: See safety information sheet (MSDS)

Tool cleaning instructions: White spirit or brush cleaner

Features: Very good anti-rust properties. Quick drying

Storage:

Minimum of 12 months in the tightly sealed original packaging in a dry, cool and frost-free place.

General: We recommend applying at temperatures between +8°C and +30°C. Do not apply in direct sunlight or when it is likely to rain. After use, close the container correctly, turn it upside down for a few seconds to prevent skin formation and then store in an upright position.

Surplus product: This paint and the packaging should be disposed of at a collection point for hazardous or special waste.