# **TECHNICAL DATA SHEET**



# **Black Tar**

**Description:** Black tar is the perfect product for treating wood, iron and concrete that needs to be protected against the weather and the permanent ingression of water. Highly suitable for materials situated below ground level. Can be applied to wood that has already been treated with carbolineum, iron that has been treated with black varnish and concrete that has been treated with coal tar. Black tar is non-toxic after drying. Black tar cannot be painted over with paint. For exterior use.

## **Application**

Apply in thin coats using a brush, tar brush or roller.

**Dilute with:** Ready to use, dilute with approximately 10% white spirit if required.

**Covers**: Approximately 8 m2 per litre, heavily dependent on the coating thickness and the structure of the surface to be treated.

**Drying time at 23°C** Drying time at 23°C: Heavily dependent on the coating thickness applied. Dust dry after approximately 6-8 hours. Apply next coat after 24 hours.

#### SYSTEM CONSTRUCTION

#### Preparation

The substrate must be dry and free from grease. Remove old poorly adhering layers on wood and sand using sandpaper.

Clean concrete and iron and roughen with a wire brush.

**TECHNICAL DATA** 

Dilute with: Ready to use

Hazard classification: See safety information sheet

(MSDS)

## Tool cleaning instructions:

It is recommended to use disposable brushes.

**Storage:** Minimum of 12 months in the tightly sealed original packaging in a dry, cool and frost-free place.

#### **General information**

Do not use in temperatures below 10°C, in direct sunlight or when rain or fog is expected. Replace lid firmly after use and store in a cool and frost-free place.

Harmful particles may be released when sanding or scraping off coats of paint, etc.. Work in a well-ventilated area and use the correct protective equipment if necessary.

**Warning:** Used rags and cloths can ignite if they become overheated. Always spread them out and leave outside to dry or pour water over them.

**Surplus product:** This product and the packaging should be disposed of at a collection point for hazardous or special waste.