# TECHNICAL DATA SHEET

## **Sleeper Black**

**Description:** Black protective coating for sleepers and border roll fencing, can be applied to surfaces treated with carbolineum. Particularly resistant to water, alkalis and acids, making it ideally suitable for the protection of concrete objects such as silos, etc.. Does not burn the skin or plants. Finess Black Tar is more suitable for objects situated below ground level. For exterior use.

#### Application

Stir thoroughly before and during use in order to ensure that any pigment particles which may have settled are evenly redistributed. Apply 1 or 2 thin coats using a brush, tar brush or roller. Less suitable for surfaces used for sitting on or walking on. Because sleeper black contains bitumen, it cannot be painted over.

Dilute with: Ready to use.

**Covers**: Heavily dependent on the coating thickness and the structure of the surface to be treated.

**Drying time at 23°C:** Dust dry after approximately 4-6 hours. Apply a second coat after 24 hours if required.

SYSTEM CONSTRUCTION

#### Preparation

The substrate must be dry and free from grease. First clean with water and ammonia. Leave to dry, sand lightly and remove any dust.

## TECHNICAL DATA

Dilute with: Ready to use

Hazard classification: See safety information sheet (MSDS)

## **Tool cleaning instructions:**

It is recommended to use disposable brushes.

**Storage:** Minimum of 12 months in the tightly sealed original packaging in a dry, cool and frost-free place.

# General

Do not use at temperatures below 10°C, in direct sunlight or when rain or fog is expected. Replace lid firmly after use and store in a cool and frost-free place. Harmful particles may be released when sanding or scraping off coats of paint, etc.. Work in a well-ventilated area and use the correct protective equipment if necessary.

**Warning:** Used rags and cloths can ignite if they become overheated. Always spread them out and leave outside to dry or pour water over them.

**Surplus product:** This product and the packaging should be disposed of at a collection point for hazardous or special waste.