

Description: Extra durable, high-gloss modified alkyd resin-based varnish for wood. For internal and external use.

Application:

Specially designed for wood that has been exposed to water and weather such as door and window frames, gates etc.

Properties:

- High gloss.
- Durable
- Weather-resistant
- Can be diluted with white spirit

Handling:

Stir thoroughly prior to use. Apply with a flat brush, paint roller or a spraying device in the direction of the grain. On untreated wood, dilute the first layer with 5-10% white spirit to improve penetration. Do not dilute the second and third layers. After every layer, lightly sand in the direction of the grain and carefully ensure it is free of dust.

Covers:

approx. 16 m² per litre per layer.

Drying time at 23°C and rel. humidity 65%:

Dust-dry: After approx. 4 hours.

Can be painted over after approx. 18 hours.

SYSTEM CONSTRUCTION

Substrate:

The surface must be clean, dry and free from dust or grease. Completely remove poorly adhering varnish layers.

Untreated wood:

Degrease with water and ammonia, lightly sand and remove dust. Finish inside with 2 layers. Outdoor: finish with at least 3 layers of Yacht Varnish.

Varnish layers in good condition:

Carefully remove any grease using a degreasing agent, scrub gently and remove dust. Finish with 1 or 2 layers of Yacht Varnish.

Varnish layers in poor condition:

Completely remove varnish layers by sanding and/or scraping. Next, treat as 'Unprimed wood'.

TECHNICAL DATA

Binding agent: Alkyd/comb. of alkyd and urethane modified alkyd resin

Solvent: White spirit

Solid components: 48% in weight

S.G.: approx. 0,910

Viscosity: Din 4: 120 sec.

Recommended coat thickness: 35 microns per layer

Gloss degree: 90% with Gardner 60°C gloss meter

Tint: Colourless

Dilution: White spirit

Flash point: Approx. 39°C

Hazard classification: See safety information sheet (MSDS)

Tool cleaning instructions: White spirit or brush cleaner.

Storage: Minimum of 12 months in the tightly sealed original packaging in a dry, cool and frost-free place.

General: We recommend applying at temperatures between 8°C and 30°C. Do not apply in direct sunlight or when it is likely to rain. After use, close the container correctly, turn it upside down for a few seconds to prevent skin formation and then store in an upright position.

Surplus product: This paint and the packaging should be disposed of at a collection point for hazardous or special waste.