

### Description

Fluor Multimarker is a high-visibility marker paint. Can be used as a multifunctional marker in construction to show where holes need to be drilled, for example, or where pipes should be installed etc. Equipped with a special spray nozzle head that allows the user to 'write' with the paint. Life of 8 - 12 months, excellent hiding capability, weather-resistant and high resistance to mechanical stress. Does not contain toluene or xylene. Suitable for use on substrates such as metal, concrete, stone, wood, brickwork, etc.

### Properties

- Quick drying
- Fluorescent
- Excellent adhesion
- 360° spray nozzle

### Substrate:

The surface must be clean, dry and free from grease. Remove any rust and old, flaking coats of paint. Remove all moss and algal growth. Mask off the surrounding area.

### Application

Allow the spray can to reach ambient temperature. The ideal application temperature is 15 to 25°C. Before use, agitate the spray can vigorously for 2 minutes and spray a test surface. Also agitate the spray can occasionally during use. Apply from a distance of approximately 25 to 30 centimetres. The special nozzle means that the spray can be used in all spraying positions.

**Covers:** Approx. 1-2 m<sup>2</sup> per 500 ml, depending on the surface and application.

### Drying time at 23°C and relative humidity of 65%:

Dust-free: After 5 to 10 minutes

Tack-free: after 10 to 20 minutes

Cured/ready for further coating: After 24 hours

**The drying time depends on the ambient temperature, the relative humidity and the coating thickness.**

### TECHNICAL DATA

<b>Content:</b>	500 ml
<b>Basis:</b>	Acrylic resin
<b>Colour:</b>	Various colours
<b>VOC content:</b>	Approximately 87 m/m %
<b>Solid components:</b>	Approximately 13 m/m %
<b>Heat resistance :</b>	up to 110°C
<b>Hazard classification:</b>	See MSDS

**Storage:** Minimum of 12 months in the tightly sealed original packaging in a dry, cool and frost-free place.

**General:** Do not use at temperatures below 10°C. Do not use outside when it is likely to rain, frost is expected, or in direct sunlight. The spray can must be kept at room temperature (minimum of 15°C). Never place the spray can on a heat source.

**Surplus product:** This paint and the packaging should be disposed of at a collection point for hazardous or special waste.