

Description: Texture paint with fine wood fibres, based on a synthetic resin dispersion. Good coverage and breathable. Application by roller or spray equipment. For interior use.

Use: Suitable surfaces include: existing coats of paint, cement and plasterwork, concrete, brick, gypsum panelling, board, etc.

Properties:

- Good hiding capacity
- Easy to apply
- Decorative
- Washable
- Breathable

Colour: White and can be tinted using universal colour pastes.

Application:

Stir thoroughly prior to use. The first coat can be diluted with a maximum of 10% water. Apply in 1 or 2 coats using a suitable paint sprayer, paint roller or brush. Always work wet-on-wet to prevent visible marks in the paint. Back-roll all overlaps in the same direction.

Spraying:	HVLP
Nozzle opening	3 – 6 mm.
Air pressure	Approx. 6 bars
Dilute	-

The stated settings for spraying this product should be taken as your starting point. Depending on the on-site conditions, the settings will have to be determined by the person applying the paint.

Covers:

Fine = approx. 2 m²/litre.

Medium = approx. 1.5 m²/litre.

The stated coverage is theoretical. The actual coverage depends on the nature and the structure of the surface and the application method.

Drying time at 23°C and relative humidity of 65%:

Dry after approximately 2 hours.

Can be painted over after approximately 6 hours.

SYSTEM BUILD-UP

General:

The surface must be capable of supporting the paint, completely set, clean, dry, and free from dust or grease. Sand and repair surface irregularities. Remove and/or repair all loose and unstable coats.

New, untreated substrates

- Prime (highly) absorbent surfaces in their entirety using SPS Transparent primer.
- Thoroughly clean powdery surfaces. Prime using Fixator after allowing to dry.

Existing intact coats of wall paint

- Clean.
- Apply an intermediate coat of SPS Projecttex 1010 if necessary.

Existing, flaking coats of wall paint

- Remove loose parts.
- Thoroughly wash powdery coats and allow them to dry.
- Carry out any repairs.
- Prime with SPS Fixator.

Stains caused by nicotine, damp, rust or soot

- Clean thoroughly using SPS Paint cleaner.
- Treat surface/stain with SPS Insulator.

The systems described above apply for the most common types of surface. For specific applications and/or detailed advice, please contact SPS bv.

TECHNICAL DATA (applies to white)

Binding agent:	Synthetic resin dispersion
Pigments:	Rutile titanium dioxide, fine fillers and wood fibres
Solvent:	Water
Specific mass:	Approx. 1.6 g/ml
Degree of gloss:	Matt, <10% @85°
VOC content	< 20 gr/l
Dilute with:	Water
Hazard classification:	See MSDS
Tool cleaning instructions:	Use water and soap.

Shelf life: Minimum of 12 months in the tightly sealed original packaging in a dry, cool and frost-free place.

General:

The values stated in this technical data sheet have been determined based on DIN EN 13300. Do not apply at temperatures below +8°C. Only apply if the surface temperature is at least 3°C above the dew point temperature. Always use the required personal protective equipment when applying this product. Do not inhale spray mist/fumes given off by products. Always ventilate appropriately when applying.

Surplus product: This paint and the packaging should be disposed of at a collection point for hazardous or special waste.