

**Description:** Universal, fast drying, excellent adhesion primer based on a water-based polyurethane acrylate dispersion.

**How to use:** Provides excellent adhesion to various surfaces such as: wood, MDF, PVC, and non-ferrous metals (e.g. zinc and aluminium).

**Properties:**

- Perfect adhesion
- For many substrates
- Dries quickly

**Colour:** White and grey.

**Application:** Stir well before use. Apply in one or more layers with a suitable brush or roller. Water-based products dry relatively quickly. To avoid starting, always work wet-on-wet. Do not touch up during drying. Lightly sand between the layers and make them dust-free.

**Covers:** Approx. 13 m<sup>2</sup> /litre per layer. The specified yield is theoretical. Actual consumption depends on the nature and structure of the substrate and the processing method.

**Drying time at 23°C and relative humidity of 65%:**

Dry after approx. 1 hour.

Can be painted after approx. 6 hours.

PAINT SYSTEM

**General:**

The substrate must be load-bearing, clean, dry, dust and grease free. For good edge coverage, the sharp corners should be slightly rounded off.

**Untreated wood and MDF:** Degreasing, light sanding and dust removal. Then apply 2 layers of SPS Uni-Primer. If necessary, fill in and then sand. Touch up the filled surfaces.

**Galvanised steel and non-ferrous metals:** Degreasing, removing rust and dust, then sanding with steel wool and cleaning thoroughly and making it dust-free.

**Hard plastic:** Degreasing, sanding and dust removal.

The systems mentioned are used as a general description for the most common substrates. For specific applications and/or extensive advice, please contact SPS bv.

TECHNICAL DATA (applies to white)

Solvent:	Water
Solid components:	38 % v/v
Specific mass:	ca. 1,35 g/ml
Dilute with:	Water
Hazard classification:	See MSDS
Tool cleaning instructions:	Use water and soap

**Shelf life:**

Minimum of 12 months in the tightly sealed original packaging in a dry, cool and frost-free place.

**General:**

Do not apply at temperatures below +8°C. Only apply if the surface temperature is at least 3°C above the dew point temperature. Do not apply outdoors when it is likely to rain, when frost is expected or in direct sunlight. Always use the required personal protective equipment when applying this product. Always ventilate appropriately when applying.

**Surplus product:**

This paint and the packaging should be disposed of at a collection point for hazardous or special waste.